



PRODUCTS FROM AMPCO











FOR TRADE ENQUIRES CONTACT:



AUTOMOTIVE PRODUCTS COMPANY FZCO

Address: POBOX No. 342001 IFZA Business Park, DDP, United Arab Emirates

E-mail: rag@ampcodubai.com **Website:** www.ampcodubai.com

Phone: U.A.E.+971 54 784 5815





SHOCK ABSORBERS



COVERING FULL RANGE -AMERICAN -EUROPEAN-JAPANESE-KOREAN-CHINESE VEHICLES MORE THAN 8600 PART NUMBERS COVERED

MANUFACTURED BY STATE OF THE ART NO 1 OEM AND AFTER MARKET - FACTORY FROM CHINA





NOK Oil Seal

FOR TRADE ENQUIRES CONTACT:



AUTOMOTIVE PRODUCTS COMPANY FZCO

Address: POBOX No. 342001 IFZA Business Park, DDP, United Arab Emirates

E-mail: rag@ampcodubai.com **Website:** www.ampcodubai.com

Phone: U.A.E.+971 54 784 5815



AMPCO SHOCK ABSORBERS

PRECISION, PERFORMANCE, PROTECTION.

ABOUT AMPCO

AMPCO is the house brand of AMPCO DUBAI a well-connected Trading company in providing high-quality automotive product solutions to customers globally, Our products gives unmatched performance, safety, and reliability. We also Promote LUCAS and GIRLING branded Products in GCC

ABOUT SHOCK ABSORBERS

Automotive shock absorbers play a crucial role in vehicle suspension systems, enhancing comfort, control, and safety. Choosing the right type and quality shock absorbers is Critical in ensuring an Excellent suspension system for any vehicle. When you use AMPCO shock Absorbers you are in a safe Zone.

AMPCO SHOCK ABSORBERS helps with Enhanced handling and braking, reducing the risk of accidents, thus ensuring safety. It absorbs road irregularities for a smoother ride by ensuring Comfort. It reduces uneven tire wear by maintaining consistent road contact, thereby increasing tire life. It also prevents excessive strain on suspension components.

WHY PARTNER WITH AMPCO DUBAI?

Proven Track Record: AMPCO products is used by many customers, earning us a reputation for quality and reliability.

Innovative Marketing Support: Full access to marketing collateral, and sales materials,

Dedicated Customer Service: Tailored support for distribution partners to ensure smooth operations and growth. **Competitive Pricing:** Competitive pricing models that ensure profitability for all channel partners and customers.

WHAT ARE THE FUNCTIONS OF SHOCK ABSORBERS?

Damping Vibrations: Control the motion of springs and suspension to prevent excessive bouncing.

Absorbing Energy: Convert kinetic energy from road impacts into heat, dissipating it to stabilize the vehicle.

Maintaining Tire Contact: Tailored support for distribution partners to ensure smooth operations and growth.

Competitive Pricing: Keep tires firmly in contact with the road for better traction and braking.

Improving Ride Comfort: Minimize road noise and vibration transmitted to the cabin.

Enhancing Vehicle Control: Prevent vehicle swaying or leaning during cornering or braking.

MORE ON SHOCK ABSORBERS

FEATURES OF SHOCK ABSORBERS

- 1. **Twin-tube Design:** Determines how the absorber manages oil and gas pressures.
- 2. Adjustability: Some shock absorbers allow for stiffness adjustments to suit different driving conditions.
- 3. Material Composition: High-quality steel construction for durability.
- 4. Gas-Filled or Hydraulic: Different mediums (gas or oil) are used for damping.
- 5. Self-Leveling Capability: Found in advanced systems to adjust ride height dynamically.
- **6. Seal Quality:** High Quality Seal Prevents oil leaks and maintains performance over time ,Oil seal used inside AMPCO shock absorber is NOK oil seal TOP quality one from Japan

7. Damping test: 100% damping force test before delivery.



AMPCO SHOCK ABSORBERS

PRECISION. PERFORMANCE. PROTECTION.

TYPE OF SHOCK ABSORBERS

1. Hydraulic Shock Absorbers

Use hydraulic fluid for damping. Reliable and straightforward design.

2. Gas-Charged Shock Absorbers:

Contain pressurized nitrogen gas in addition to oil.Reduce foaming and provide consistent performance, especially at high speeds.

3. Mono-Tube Shock Absorbers:

Single-tube design. Better heat dissipation, ideal for performance applications. especially at high speeds.

Twin-Tube Shock Absorbers: Dual-tube design (inner and outer tubes). Common in passenger cars for comfort-oriented rides.

Coilover Shock Absorbers: Combine a spring and shock absorber into one unit.Common in sports and racing vehicles for precision handling.

Air Shock Absorbers: Use air as a medium to support the load. Frequently found in luxury vehicles for smooth, adjustable rides.

Electronic Shock Absorbers: Controlled by an electronic module that adapts damping force in real-time. Found in modern high-tech vehicles.



FOR TRADE ENQUIRES CONTACT:



AUTOMOTIVE PRODUCTS COMPANY FZCO

Address: POBOX No. 342001

IFZA Business Park, DDP, United Arab Emirates

E-mail: rag@ampcodubai.com Website: www.ampcodubai.com

Phone: U.A.E.+971 54 784 5815




AMPCO SHOCK ABSORBERS

PRECISION, PERFORMANCE, PROTECTION.

CARTON AND PACKING DETAILS



Carton Design





Box Label Design

FOR TRADE ENQUIRES CONTACT:





AMPCO BRAKE FLUID

PRECISION. PERFORMANCE. PROTECTION.

ABOUT AMPCO

AMPCO is the house brand of AMPCO DUBAI a well-connected Trading company in providing high-quality automotive product solutions to customers globally ,Our brake fluid gives unmatched performance, safety, and reliability. We also Promote LUCAS and GIRLING branded Products in GCC

FEATURES

- **High-Performance Formulation:** Optimized for maximum braking efficiency under high temperatures.
- **Superior Corrosion Protection:** Protects metal components against rust, ensuring longer vehicle life.
- **Wide Compatibility:** Suitable for all hydraulic brake and clutch systems.
- DOT Compliant: Adheres to specifications of international safety standards including DOT 3 and DOT 4.
- Available in 250ML/500ML packed in 24 CANS cartons
- Extreme Weather Resistance: Performs well even under the harshest GCC conditions, including extreme heat.

TECHNICAL SPECIFICATION DOT 3				
Density @ 20°c	1.030			
Appearance	C & B			
Viscosity, cST @ 40°c	Max. 1200			
Viscosity, cST @ 100°c	Min. 1.90			
ERBP°c (dry)	225-230			
ERBP°c (wet)	135-140			
ph Value	8.0			
Color	Natural			







WHY PARTNER WITH AMPCO DUBAI?

- **Proven Track Record:** AMPCO's brake fluid is used by many customers, earning us a reputation for quality and reliability.
- Innovative Marketing Support: Full access to marketing collateral, and sales materials,
- Dedicated Customer Service: Tailored support for distribution partners to ensure smooth operations and growth.
- Competitive Pricing: Competitive pricing models that ensure profitability for all channel partners and customers.

FOR TRADE ENQUIRES CONTACT:



AUTOMOTIVE PRODUCTS COMPANY FZCO

Address: POBOX No. 342001
IFZA Business Park, DDP, United Arab Emirates

IFZA Business Park, DDP, United Arab Emirates

E-mail: rag@ampcodubai.com **Website:** www.ampcodubai.com

Phone: U.A.E.+971 54 784 5815







AUTOMOBILE BATTERY

FOR TRADE ENQUIRES CONTACT:



AUTOMOTIVE PRODUCTS COMPANY FZCO Address: POBOX No. 342001

IFZA Business Park, DDP, United Arab Emirates

 $\textbf{E-mail:} \ \mathsf{rag@ampcodubai.com} \ \textbf{Website:} \ \mathsf{www.ampcodubai.com}$

Phone: U.A.E.+971 54 784 5815

ampcodubai.com **Made in Vietnam**



ABOUT AMPCO

AMPCO is the house brand of AMPCO DUBAI a well-connected Trading company in providing high-quality automotive product solutions to customers globally ,Our Products gives unmatched performance, safety, and reliability. We also Promote LUCAS and GIRLING branded Products in GCC

AUTOMOBILE BATTERY

We offer a complete line of maintenance-free lead-acid batteries for passenger cars.

Our precision-focused manufacturing facilities use state-of-the-art technology to ensure that our batteries deliver high performance and a smooth driving experience.

We manufacture premium maintenance-free automotive batteries for heavy-duty commercial vehicles.

These vehicles need batteries that are exceptionally robust and powerful to meet the heavy-duty demands placed on them round the clock under all sorts of terrain and weather conditions.





BEST FIT FOR TROPICAL ENVIRONMENT



EXPANDED METAL TECHNOLOGY



SILVER INSIDE



LONGER LIFE



THICKER PLATE



JIS TYPE

Passeng	er Car	AH@20	001	Dim	Dimension(mm)		Cell				
Old JIS	New JIS	Hour Rate	CCA	L	W	Н	Layout				
PASSENGER CAR											
NS40/L	36B20R/L	32	350	197	129	227	1/2				
NS40Z/L	44B20R/L	35	400	197	129	227	1/2				
N40/L	50B24R/L	40	420	238	129	227	1/2				
N40S/LS	50B24R(S)/L	(S) 40	420	238	129	227	1/2				
NS60/L	55B24R/L	45	460	238	129	227	1/2				
NS60S/LS	55B24R(S)/L	S 45	460	238	129	227	1/2				
55D23/L	65D23/L	60	570	231	173	225	1/2				
N50/L	55D26R/L	50	480	259	173	225	1/2				
N50Z/ZL	65D26R/L	60	550	259	173	225	1/2				
NS70/L	80D26R/L	65	630	259	173	225	1/2				
NX110-5/L	85D26R/L	70	675	259	173	225	1/2				
N70/L	85D31R/L	70	650	306	173	225	1/2				
N70Z/ZL	95D31R/L	75	710	306	173	225	1/2				
NX120-7/L	105D31R/L	80	780	306	173	225	1/2				
N90/L	115D31R/L	90	800	306	173	225	1/2				
		C	OMME	RCIAL	VEHIC	LE					
N100/L	115E41R/L	100	830	410	173	233	1/2				
N120/L	135F51R/L	120	950	506	182	250	1/2				
N135/L	150F51R/L	135	1050	506	182	250	1/2				
N150/L	165G51R/L	150	1200	506	221	248	1/2				
N170/L	190G51R/L	170	1300	506	221	248	1/2				
N180/L	195H52R/L	180	1350	518	274	248	1/2				
N200/L	210H52R/L	200	1400	518	274	248	1/2				



DIN TYPE PREMIUM

	AU 620		Dimension(mm)			Cell	-	Hold		
Battery Type	AH@20 Hour Rate	CCA	L	W	Н.	Layout	Terminal Type	Down		
54434/54459	44	420	207	175	190	2	С	B13		
55530/55548	55	510	242	175	190	2/1	С	B13		
56030/56031	60	620	242	175	190	2/1	С	B13		
56618/56638	66	640	278	175	190	2	С	B13		
57217/57219	72	765	278	175	190	2	С	B13		
57412/57413	74	765	278	175	190	2/1	С	B13		
57512/57513	75	765	278	175	190	2/1	С	B13		
58533/58535	85	860	315	175	190	2	С	B13		
58035/58043	80	860	315	175	190	2	С	B13		
58815/58827	88	900	353	175	190	2	С	B13		
59218/59259	92	900	353	175	190	2/1	С	B13		
60038/60044	100	950	353	175	190	2	С	B13		
LOW HEIGHT SERIES										
54321/54322	43	410	207	175	175	2/1	С	B13		
55046	50	480	242	175	175	2	С	B13		
55419/55457	54	480	242	175	175	2	С	B13		
55506	55	480	242	175	175	2	С	B13		
58014	80	820	315	175	175	2	С	B13		
DIN CV										
67018	170	875	509	222	175	4/3	Α	-		
68032	180	1000	509	222	175	4/3	Α	-		
72527	225	1300	505	264	175	4/3	Α	-		



KEY PRODUCT FEATURES

Calcium-calcium-tin and calcium-silver maintenance-free

battery

Expanded metal grid technology


Centered cast-on-strap cells

Double chamber container with condensation mechanism

Built-in magic eye and flame arrestor

Best grade virgin lead, pp, and chemicals


Robust design to perform in all terrain conditions



SELF - DISCHARGE CHARACTERISTICS

Self-discharge by nature is a common phenomenon for lead-acid batteries. The reason behind this is the impurities contained in lead alloy induce local action, causing electric energy to be consumed. This phenomenon is temperature dependent; higher temperature leads to higher discharge. Compared with other lead-acid batteries, GLOBATT uses carefully selected highly refined Ca-Tin alloy, rendering an extremely low rate of self-discharge. That's why a freshening charge is not required for GLOBATT batteries until the OCV becomes 12.2V or lower.

Fig: Self - Discharge Characteristics



At 12.2 V lastest recharge in needed

37°C= 7 month 12.2V 30°C=11 month 12.2V 23°C=18 month 12.2V 15°C=30 month 12.2V





2W ENGINE OIL



ABOUT AMPCO

AMPCO is the house brand of AMPCO DUBAI a well-connected Trading company in providing high-quality automotive product solutions to customers globally ,Our products gives unmatched performance, safety, and reliability. We also Promote LUCAS and GIRLING branded Products in GCC

WHY CHOOSE AMPCO OVER OTHER BRANDS?

Known brand in the aftermarket for its quality and reliability.

Provides an extensive range of automotive products.

Products are driven by innovation.

Combining an impressive heritage with a clear commitment to providing OE-quality products now and in the future.





AMPCO 15W50 API SN 4T 1L

PERFORMANCE STANDARDS

API SN JASO Ma2

PERFORMANCE BENEFITS

Improved oil film resistance at high temperatures.

Grade 50 at hot temperatures, specifically designed for large bore engines.

Suitable for use in high-powered motorcycles.

Can be used in extreme weather conditions.

Lower maintenance costs with HF3 (Hassle-Free

Technology) featuring high friction modifiers, high fuel economy, and high force.



Covers all major Indian-made motorcycles and scooters. Available in 210 ml, 550 ml, 2.5 L, and 1 Ltr.









AMPCO 20W40 API SN 1L

PERFORMANCE STANDARDS

API SN, JASO Ma2

PERFORMANCE BENEFITS

Lower maintenance costs with HF 3 (Hassel Free Technology) with high friction modifier, high fuel economy, and high force.

Provides smoother engine performance and gear shifts. Blended from high viscosity index synthetic-based stocks, providing protection at higher temperatures, cleaning engines, and providing better performance.



RECOMMENDATIONS

Covers all major Indian-made motorcycles and scooters. Available in 210, 55, 26, 1Ltr.








AMPCO 10W30 API SL 1L

PERFORMANCE STANDARDS

API SL, JASO MB / Ma2

PERFORMANCE BENEFITS

- Specially formulated Magnetic Engine Technology (MET), which is designed to meet the demanding lubrication requirements of modern gearless scooters.
- It provides superior protection for the engine and transmission of scooters against wear and tear.



RECOMMENDATIONS

Covers all major Indian-made motorcycles and scooters. Available in 210, 55, 26, 1Ltr, 800ml.





FOR TRADE ENQUIRES CONTACT:



AUTOMOTIVE PRODUCTS COMPANY FZCO

Address: POBOX No. 342001

IFZA Business Park, DDP, United Arab Emirates

E-mail: rag@ampcodubai.com **Website:** www.ampcodubai.com

Phone: U.A.E.+971 54 784 5815



AMPCO 20W40 API SM 1L


PERFORMANCE STANDARDS

API SM, JASO Ma2

PERFORMANCE BENEFITS

Lower maintenance costs with HF 3 (Hassel Free Technology) with high friction modifier, high fuel economy, and high forces.

Provides smoother engine performance and gear shifts.



RECOMMENDATIONS

Covers all major Indian-made motorcycles and scooters. Available in 210, 55, 26, 1Ltr, 900ml.



